

DECLARATION OF PERFORMANCE

N. 07/2013/CPR

- 1-product: Aquazero
- 2-ID: dimensions: 2000x1200x12,5 mm; 2400x1200x12,5 mm
- 3-Use: Coating of walls, ceilings and floors, both internal and external;
- 4-material: Cement board coated with glass fiber;
- 5-manufacturer: Cemtech S.r.l.
- 6- system of assessment and verification of the constancy on the performances: System 3
- 7- Performances: Ref. Following table

Essential characteristics	Performances	Reference standard
Classification to fire behavior	A1 /A1 _n	EN 13501-1
Report N. 146.0DC0050/13 of 14-02-2013; laboratory LAPI S.p.A.; CE 0987;		
Thermal conductivity	0,174 W/mK	UNI ES ISO 8990
Bulk density	1138 Kg/m ³	UNI EN 12467
Average bending on dry tests/average bending on wet tests	8,8 / 8,3 N/mm ²	UNI EN 12467
Report N.0086/13 of 14-02-2013; laboratory LAPI S.p.A.; CE 0529;		

8- The conformity assessment is carried out according to harmonized standards under Reg 305/2011 CPR. The Cemtech Srl applies the requirements regarding the assessment of the production control (FPC), as required by the quality management system, in compliance with UNI EN ISO 9001:08.

9- This declaration of performance is released under the sole responsibility of the manufacturer (ref. P.to 5)

Priverno 28-06-2013

Il Rappresentante Legale
(Timbro e Firma)

CEMTECH S.r.l.

Via Madonna delle Grazie, snc – 04015 Priverno (LT)

Tel. 0773-924224 - Fax 0773-1533642

P.IVA / C.F. 02666560590



Cert. N. AJAEU/15/13424