

DECLARATION OF PERFORMANCE

In accordance with EU Construction Products Regulation (CPR) № 305/2011

№ DoP-CPR-BG-460P-074

1. *Unique identification code of the product-type:*

weber 460P

2. *Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:*

Mixture for gluing and plastering EPS (expanded polystyrene) and XPS (extruded polystyrene) boards.

3. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11 (5):*

SAINT GOBAIN CONSTRUCTION PRODUCTS BULGARIA EOOD
Division Weber
Industrialna zona, Poletto 6
2230 Kostinbrod, Bulgaria
Phone.: +359 2 400 37 00; Fax: +359 2 400 37 05
e-mail: office@weber.bg; web: www.weber.bg

4. *Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):*

Not applicable

5. *System or systems of assessment and verification of consistency of performance of the construction product as set out in Annex V:*

The product is assessed according to system 4, Annex V.

6. *In case of the declaration of performance concerning a construction product covered by a harmonized standard:*

Complies with EN 998-1:2010

The assessment is carried out by NISI EOOD - NB 2032 and the initial type test report is # 799-3-268/12.11.2014.

The product, for which this declaration is issued is produced under production control, established and maintained by the producer.

7. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*

Not applicable

8. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 998-1:2010
Water absorption	W2	
Water vapor permeability	$\mu \leq 22,8$	
Thermal conductivity (at P=50%)	$\lambda_{10,dry,mat} \leq 0,55 \text{ W/mK}$	
Thermal conductivity (at P=90%)	$\lambda_{10,dry,mat} \leq 0,60 \text{ W/mK}$	
Tensile adhesion strength with concrete	$\geq 0,25 \text{ N/mm}^2$	
Tensile adhesion strength with EPS	$\geq 0,08 \text{ N/mm}^2$	
Dangerous substances	NPD	

NPD = no performance determined

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

10. Signed for and on behalf of the manufacturer by:

Snejana Semova
General Manager of Saint Gobain Construction Products Bulgaria EOOD

(name and function)

Kostinbrod, Bulgaria, 10.12.2014

(place and date of issue)

(signature)

